

## AMENDMENTS TO THE CLAIMS

Please amend the claims as follows:

1. (original) A method comprising:

encoding a digital signal in a manner that reduces variations over time in a collective signal level of the digital signal;

communicating the digital signal over a plurality of segments of signal lines; and

transposing the signal lines between the segments of signal lines in a manner that reduces differences between interline couplings of different pairs of the signal lines.

2. (original) A method as recited in claim 1, wherein the interline coupling of a particular pair of signal lines is represented as a function of the distances between said particular pair of signal lines over all the segments.

3. (original) A method as recited in claim 1, wherein the interline coupling of a particular pair of signal lines is represented as a function of a summation of the distances between said particular pair of signal lines over all the segments.

4. (original) A method as recited in claim 1, wherein the segments have approximately equal lengths.

5. (original) A method as recited in claim 1, wherein:

the segments have approximately equal lengths; and

the interline coupling of a particular pair of signal lines is represented as a function of a summation of the distances between said particular pair of signal lines over all the segments.

6. (original) A method as recited in claim 1, wherein at least two of the segments have different lengths.

7. (original) A method as recited in claim 1, wherein at least two of the segments have different lengths, the different lengths being such that they reduce differences between the interline couplings of different pairs of the signal lines.

8 (original) An interconnection for communication of a digital signal, comprising:

three or more signal lines that traverse a plurality of segments, the signal lines being configured to carry individual signals that are encoded to reduce variations over time in a collective signal level of the individual signals;

wherein there is an interline coupling parameter associated with any particular pair of signal lines that is a function of the distances between said particular pair of signal lines over all the segments; and

wherein the signal lines are transposed between the segments in a manner that reduces differences between the interline coupling parameters of different pairs of the signal lines.

9. (Currently Amended) An interconnection as recited in claim 8, wherein the plurality of segments comprises further comprising three of the segments

10. (original) An interconnection as recited in claim 8, further comprising a planar substrate upon which the signal lines are fabricated.

11. (original) An interconnection as recited in claim 8, further comprising an encoder that encodes the signals in a manner that reduces variations over time in the collective signal level of the individual signals.

12. (original) An interconnection as recited in claim 8, wherein the interline coupling parameter associated with any particular pair of signal lines is also a function of the lengths of the segments.

13. (original) An interconnection as recited in claim 8, wherein the interline coupling parameter associated with any particular pair of signal lines is a function of a summation of the distances between said particular pair of signal lines over all the segments.

14. (original) An interconnection as recited in claim 8, wherein the segments have approximately equal lengths.

15. (original) An interconnection as recited in claim 8, wherein:

the segments have approximately equal lengths, and

the interline coupling parameter associated with any particular pair of signal lines is a function of a summation of the distances between said particular pair of signal lines over all the segments.

16. (original) An interconnection as recited in claim 8, wherein at least two of the segments have different lengths.

17. (original) An interconnection as recited in claim 8, wherein at least two of the segments have different lengths, the different lengths being such that they reduce differences between the interline coupling parameters of different pairs of the signal lines.

18. (original) An interconnection as recited in claim 8, wherein the differences between the interline coupling parameters are reduced to a ratio of no greater than 2 to 1.

19. (original) An interconnection as recited in claim 8, wherein the differences between the interline coupling parameters are reduced to a ratio of no greater than 1.5 to 1.

20. (original) An interconnection for communication of a digital signal, comprising:

three or more signal lines that traverse a plurality of segments, wherein there is an interline coupling parameter associated with any particular pair of signal lines that is a function of the distances between said particular pair of signal lines over all the segments; and

wherein the signal lines are transposed between the segments in a manner that reduces differences between the interline coupling parameters of different pairs of the signal lines.

21. (Currently Amended) An interconnection as recited in claim 20, ~~further comprising wherein the plurality of segments comprises at least three of the segments.~~

22. (original) An interconnection as recited in claim 20, further comprising a planar substrate upon which the signal lines are fabricated.

23. (original) An interconnection as recited in claim 20, further comprising an encoder configured to encode the digital signal in a manner that reduces variations over time in a collective signal level on the signal lines.

24. (original) An interconnection as recited in claim 20, wherein the interline coupling parameter associated with any particular pair of signal lines is also a function of the lengths of the segments.

25. (Currently Amended) An interconnection as recited in claim 20, wherein the interline coupling parameter associated with any particular pair of signal lines is a function of a summation of the distances between said particular pair ~~of~~ of signal lines over all the segments.

26. (original) An interconnection as recited in claim 20, wherein the segments have approximately equal lengths.

27. (original) An interconnection as recited in claim 20, wherein:  
the segments have approximately equal lengths; and

the interline coupling parameter associated with any particular pair of signal lines is a function of a summation of the distances between said particular pair of signal lines over all the segments.

28. (original) An interconnection as recited in claim 20, wherein at least two of the segments have different lengths.

29. (original) An interconnection as recited in claim 20, wherein at least two of the segments have different lengths, the different lengths being such that they reduce differences between the interline coupling parameters of different pairs of the signal lines.

30. (original) An interconnection as recited in claim 20, wherein the differences between the interline coupling parameters are reduced to a ratio of no greater than 2 to 1.

31. (original) An interconnection as recited in claim 20, wherein the differences between the interline coupling parameters are reduced to a ratio of no greater than 1.5 to 1.

32. (Currently Amended) An interconnection for communication of a digital signal, comprising:

three or more signal lines forming at least three possible pairs of signal lines, a respective interline coupling parameter being associated with a respective pair of signal lines, at least two different pairs of signal lines among the possible pairs of

signal lines being transposed at respective points in the interconnection to minimize differences in interline coupling parameters associated with respective possible pairs of signal lines, that traverse a plurality of segments, wherein there is a coupling term  $C(m, n, s)$  associated with any particular pair of signal lines  $m$  and  $n$  over a particular segment  $s$ ;

wherein an interline coupling between each pair of signal lines  $m$  and  $n$  is represented as a function of  $C(m, n, s)$  for all segments  $s$ ; and

wherein the signal lines are transposed between the segments in a manner that reduces differences between the interline couplings of different pairs of the signal lines.

33. (Currently Amended) An interconnection as recited in claim 32 having a plurality of segments, wherein the three or more signal lines traverse the plurality of segments, and wherein the interline coupling parameter associated with a respective pair of signal lines  $m$  and  $n$  is a function of a sum of interline coupling terms  $C(m, n, s)$  over all segments, ~~the where~~  $C(m, n, s)$  is an interline coupling term between thea pair of signal lines  $m$  and  $n$  in is represented as the summation of  $C(m, n, s)$  over all segments  $s$ .

34. (Currently Amended) An interconnection as recited in claim ~~32~~33, wherein the coupling term  $C(m, n, s)$  is a function of the distance between signal lines  $m$  and  $n$  in over segment  $s$ .

35. (Currently Amended) An interconnection as recited in claim 32 having a plurality of segments, wherein the three or more signal lines traverse the plurality of segments and are in different orders in different segments, the coupling term  $C(m, n,$

$s$ ) is a function of the distance between signal lines  $m$  and  $n$  over segment  $s$  and of the length of segment  $s$ .

36. (Currently Amended) An interconnection as recited in claim ~~32~~33, wherein the coupling term  $C(m, n, s)$  is a function of the distance between signal lines  $m$  and  $n$  ~~over~~in segment  $s$  multiplied by the length of segment  $s$ .

37. (Currently Amended) An interconnection as recited in claim ~~32~~33, wherein the coupling term  $C(m, n, s)$  is a function the length of segment  $s$ .

38. (Currently Amended) An interconnection as recited in claim 32, ~~the three or more signal lines collectively further comprising~~having at least three of the segments.

39. (Original) An interconnection as recited in claim 32, further comprising a planar substrate upon which the signal lines are fabricated.

40. (Currently Amended) An interconnection as recited in claim 32, ~~wherein each possible pair of signal lines is transposed at most once further comprising an encoder configured to encode the digital signal in a manner that reduces variations over time in a collective signal level on the signal lines.~~

41. (Currently Amended) An interconnection as recited in claim 32, wherein the three or more signal lines including first, second and third signal lines and the at least three possible pairs of signal lines including a first signal line pair formed with



the first and second signal lines and a second signal line pair formed with the first and third signal lines, and wherein the at least two different pairs of signal lines are transposed in the interconnection to equalize as nearly as possible the interline coupling parameter associated with the first signal line pair and the interline coupling parameter associated with the second signal line pair.~~the segments have approximately equal lengths.~~

42. (Currently Amended) An interconnection as recited in claim 32, wherein the differences between the interline coupling parameters associated with any two possible pairs of signal lines~~couplings~~ are reduced to a ratio of no greater than 2 to 1.

43. (Currently Amended) An interconnection as recited in claim 32, wherein the differences between the interline coupling parameters associated with any two possible pairs of signal lines~~couplings~~ are reduced to a ratio of no greater than 1.5 to 1.